| bm | certification

CERTIFICATE OF CONFORMITY OF THE FACTORY PRODUCTION CONTROL

Approved Body No. 8520

In compliance with The Construction Products (Amendment etc.) (EU Exit) Regulations 2020 and the Construction Products (Amendment) Regulations 2022, this certificate applies to the construction product(s)

Hardwood plywood for structural use

according to Appendix A

Placed on the market under the name or trade mark of

PT. Sumber Mas Indah Plywood

and produced in the manufacturing plant at the below address Jl. Kapten Darmo Sugondo No. 99, Desa Karang Kiring, Kecamatan Kebomas, Gresik, East Java, 61124, Republic of Indonesia

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

BS EN 13986:2004+A1:2015

under system 2+ are applied and that

the factory production control is assessed to be in conformity with the applicable requirements.

This certificate was first issued on January 8, 2024 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.



Certificate number: 8520-CPR-026 Date of initial certification: January 8, 2024 Date of last issue: January 8, 2024 Certificate expiry date: January 7, 2027

Rafal Andruszkiewicz Managing director BM Certification UK

BM Certification UK Ltd, Innovation Centre, Gallows Hill, Warwick, CV34 6UW, UK This certificate remains the property of BM Certification UK Ltd. The validity of the certificate may be confirmed at the web address <u>www.bmcertification.com</u>

| bm | certification

Appendix A

 Issue No.:
 1

 Date:
 January 8, 2024

 Certificate No.
 8520-CPR-026

Hardwood plywood

unfaced

Conditions (EN636)	internal dry, internal humid and external	internal dry
Adhesive type:	Phenol Formaldehyde	Urea Formaldehyde
Formaldehyde class:	E1	E1
Thickness range:	9.0 – 40.0 mm	12.0 mm